

## ELECTRIC BAIN MARIE



Wett well bain marie with structure made of AISI 304 stainless steel, 20/10 mm thickness top. Pressed well sealed into the worktop with satin finish. Useful to containers GN 1/1 or sub-multiples. Indirect heating controlled by operation thermostat 30-90°C and safety thermostat. Containers not supplied. Provision for remote peak power cut.



<i>Energy Control</i>	Pre-Setting for remote control of power peaks	<i>Power supply</i>	Electricity
<i>Well quantity</i>	1	<i>Worktop thickness</i>	2 mm

### Functional features

- Well continuously welded to the work surface with a recess designed to contain condensate.
- Pressed well with rounded corners and slope on the bottom to facilitate discharge.
- Useful well dimension cm: 30.5 x 51 x 16 h.
- The well contains GN 1/1 containers and submultiples, h = 150 mm.
- Well capacity at minimum operating level: 6 lt.
- Thermostatic temperature control from 30° to 90°C.
- Provision for remote peak power cut.
- Pre-set appliance for installation on under compartment, support surface; with specific accessories on bridge solution and cantilever on beam.

### Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Control panel made in AISI 304 stainless steel, thickness 12/10 mm, Scotch-Brite finish. Side paneling made in AISI 304 stainless steel, back panel in stainless steel.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Well in AISI 304 stainless steel thickness 10/10, pressed with rounded corners.
- Front-mounted drain cock with rotary control to prevent accidental opening.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Radiused rear splashback on the worktop h = 4 cm, with built-in chimney for heat exhaust, removable enamelled cast iron guard.
- Non-slip rubber feet h = 2 cm.
- Access to all components through front compartment or control console.

### Safety equipment and approvals

- Maximum temperature safety thermostat at minimum allowed water level (pressed on well).
- Appliance can not be used without water.
- CE approvals in respect of all current directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX4 protection rating.

### Optional

- GN containers of various sizes; crossbar to support containers; water column.

### Technical Data

<i>Working voltage</i>	400V 3N~ / 230V 3~ / 50-60 Hz	<i>Electric Power</i>	1,6 kW
<i>Dimensions</i>	40x72x25 cm	<i>Packing</i>	46x82x65 cm

ELECTRIC BAIN MARIE  
Icon 7000 prof. 700