

# 1S1FR8G



## GAS FRYER 2 WELLS 14+14 L V SHAPED

Fryer made of AISI 304 stainless steel, 20/10 mm thickness top. Pressed "V" wells - without burner in - sealed into top, generously coved with large drain zone; each well delivered with 1 basket and 1 lid. Mechanical controls. Temperature control through thermostat 100-190°C. Heat exchange pipes outside the well. Piezoelectric ignition of the pilot light, safety thermostat.



<i>Control panel</i>	mechanical	<i>Liter each well</i>	14
<i>Power supply</i>	Gas	<i>Product fitting up</i>	with integrated undercompartment
<i>Productivity</i>	28 kg/h french fries each well	<i>Well quantity</i>	2
<i>Well type</i>	Easy Cleaning - "shaped well"	<i>Worktop thickness</i>	2 mm

### Functional features

- Gas fryer 2 wells made in AISI 304 stainless steel - capacity 14 + 14 lt.
- Large recess in the upper section for oil expansion with the same capacity of the well.
- Well with special shape "V" type, exchange pipes positioned outside the well for an improved and full cleaning.
- Cuve designed with cold area for collecting cooking residues.
- Heating by means of burners out of the well.
- Heat exchange surface area calculated for specific output of no more than 5 watt/cm<sup>2</sup> for a longer oil life.
- Fried potatoes productivity (base on AGA standards A.G. 309 - 1994 (M.O.T. 2.1.1 - 88): 14 kg/h per well.
- Temperature control by thermostat with bulb in the well, to guarantee an immediate response to the temperature change, from 100 to 190°C.
- Piezo-electric ignition of the pilot light.
- Basket hanger for dripping.
- Pre-set appliance for installation freestanding on feet; with specific accessories on cantilever on beam.

### Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Control panel made in AISI 304 stainless steel, thickness 12/10 mm, Scotch-Brite finish. Side paneling made in AISI 304 stainless steel, back panel in stainless steel.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Oil drain pipe fixed to well, with ball-valve tap fitted with heat-resistant handle.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Radiused rear splashback on the worktop h = 4 cm.
- Chimney for heat exhaust, h = 25 cm, with removable enamelled cast iron guard.
- Lower compartment with two doors.
- Hinged doors, with sandwich panel, made in AISI 304 stainless steel, grip directly pressed on the door plate, easy to clean.
- Height adjustable floor-mounted feet in AISI 304 stainless steel, non-scratch sole in insulating plastic material. Feet are supplied at a fixed height of 15 cm. Foot extension 5 cm (minimum height / maximum height: 87.5 / 92.5 cm).
- Access to all components through front compartment or control console.

### Safety equipment and approvals

- Security control on gas operation ensured by thermostatic valve, pilot light and thermocouple.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).

### Standard equipment

- Each well delivered with: nr. 1 basket made in chromed steel dimensions in cm 22.5 x 28.3 x 11.5.



# 1S1FR8G



- Well lid in AISI 304 stainless steel full covering of the well.
- Chromium-plated steel bottom mesh with basket support outside the well.
- Oil drainage line extension for safe and easy oil drainage of oil, even when hot, away from the fryer itself.

## Optional

- Single full well basket; 2 chromed stainless steel baskets for well dimensions of each basket in cm: 11.2 x 28.8 x 11.5.
- Oil filter, oil drain container.
- Wheels.

## Technical Data

<i>Gas Power</i>	28 kW	<i>Dimensions</i>	80x72x90 cm
<i>Packing</i>	86x82x130 cm		

GAS FRYER 2 WELLS 14+14 L V SHAPED  
Icon 7000 prof. 700

